

UBERLUB HD 40-50-60 SERIES (MARINE TBN 40)

UBERLUB HD 40-50-60 SERIES are the mono grade viscosity engine oils that meet the CF/SL standard of API performance classes. High performance base oils and non-ash dispersing additives are heavy duty, single season diesel engine oils, formulated with metallic detergents and a balanced additive system that prevents oxidation, abrasion, corrosion and corrosion. It is a high-performance marine diesel oil, formulated with special additive package and high quality base oils.

CHARACTERISTICS (TYPICAL VALUES)

UBERLUB HD 40-50-60 SERIES	40	50	60	
Specific Gravity @ 15°C	0.879	0.887	0.9	
Flash Point °C.	205	228	240	
Viscosity cSt @ 100 °C	15.5	18.9	24,5	
Viscosity cSt @ 40 °C	152	178	265	
VI	104	110	117	
Pour Point, °C.	-26	-24	-21	
TBN (D-2896)	40	40	40	

The values given above may change due to research and development studies.
Production from production may show slight variations in typical characteristics.

Health, Safety and Environmental Information

The product is not expected to have adverse effects on human health, as long as it is used in accordance with the instructions and the recommendations provided in the Safety Data Sheet (MSDS). It is recommended that a person who is constantly in contact with the product should wear protective equipment. Used oil must not be poured into the soil and waste water channels. Used products T.C. Recycling should be provided or disposed of as specified in the Ministry of Environment and Forestry's Waste Oil Control Regulation.



0264 275 8649



www.uberlub.com.tr



Hanlı Merkez Mah. 22 Nolu Sk. No: 43 / Z1 Arifiye / Sakarya

UBERLUB HD 40-50-60 SERIES (MARINE TBN 40)

PROPERTIES AND PERFORMANCES

- Protect the motor against cylinder wear, ring and bearing wear.
- Provides superior protection against corrosion thanks to high total base number (TBN).
- Because of its excellent detergent / dispersing properties, it minimizes sedimentation and drying of the piston and piston rings.
- Increases the life of the engine by reducing deposits and soot formation the least.
- Provides maximum wear protection in warm climates

INTERNATIONAL SPECIFICATIONS

API

CF / CF-2, CF-4
CF, CD
SL



0264 275 8649



www.uberlub.com.tr



Hanlı Merkez Mah. 22 Nolu Sk. No: 43 / Z1 Arifiye / Sakarya